



## WXGA ultra-short-throw projector with built-in interactivity and a host of connectivity options

The D755WTi is Vivitek's new compact ultra-short-throw projector with built-in interactivity function which make possible to turn any standard screen or white surface into an interactive projection solution. The D755WTi delivers high brightness with 3,300 ANSI Lumens and an outstanding contrast ratio of 5000:1 for a perfectly displayed image. The D755WTi is a stylish projector that is future proof with direct 3D via HDMI, powerful 20W built-in speaker and an assortment of connectivity options include HDMI v1.4 for perfect digital image transmission and RJ-45 for network connectivity, the D755WTi is the ultimate education projector for perfect presentations.

### Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Built-in IWB functionality with interactive pens
- Dual pen support for simultaneous use
- Delivers a large 80" to 100" image from a ultra-short distance
- Helps prevent shadow obstruction and light glare in the presenter's eyes
- Bright 3300 ANSI lumens with a colorful 5000:1 contrast ratio
- Energy efficient lamps that last up to 10.000 hours (in economy mode)
- DisplayPort connector for digital audio and video signals
- Network ready for integration and system administration via RJ45
- VGA-output for display on a secondary monitor
- Powerful 20W audio speaker
- Top-loading, cover for quick and easy lamp replacement
- Sealed optical engine, minimizing the impact of dust and smoke
- Keypad lock prevents accidental system adjustments

### Product Pictures



| Specifications         |  |
|------------------------|--|
| Display Type           | DLP  |
| Brightness             | 3300 ANSI Lumens   |
| Native Resolution      | WXGA (1280 x 800)  |
| Maximum Resolution     | UXGA (1600 x 1200)   |
| Contrast Ratio         | 5000 :1  |
| Lamp Life and Type     | 6,000/10,000 Hours (Std./ Eco Mode) 230W   |
| Image Size (Diagonal)  | 80"- 100"  |
| Projection Lens        | Manual Focus   |
| Zoom Ratio             | Fixed Lens   |
| Aspect Ratio           | 16:10 Native   |
| Throw Ratio            | 0.35:1   |
| Offset                 | 280mm-337mm +/-50mm  |
| Keystone Correction    | Vertical ± 40°   |
| Horizontal Frequency   | 15, 30-91.4KHz   |
| 3D Ready               | Direct 3D via HDMI   |
| Vertical Scan Rate     | 43 - 87Hz  |
| Speakers               | 20W  |
| Lens Shift Range       | N/A  |
| Video Compatibility    | SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)   |
| I/O Connection Ports   | HDMI v1.4, VGA-In (x2), DisplayPort, S-Video, Composite, Audio-In RCA, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, 3D-Sync Out, RS-232C, USB (interactivity and service) |
| Projection Method      | Table Top, Ceiling Mount (Front or Rear)   |
| Security Solutions     | Kensington® Security Slot, Security Bar, Keypad Lock   |
| Dimensions (W x D x W) | 288 x 374 x 127mm  |
| Weight                 | 5Kg  |
| Noise Level            | 29dB/33dB (Eco / Normal Mode)  |
| Power Supply           | AC 100-240V, 50/ 60Hz  |
| Power Consumption      | 240W (Eco Mode), 290W (Normal Mode), <0.5W (Standby Mode)  |
| Warranty               | 3 Years, 1 Year (or 1,000h) on the Lamp  |
| Education Warranty     | 5-Year Warranty, 3-Year (or 2,000 hours)   |
| Standard Accessories   | AC Power Cord, VGA Cable, Remote Control, Interactive Pen (x2), Documentation Kit  |
| Optional Accessories   | Replacement Lamp, Remote   |
| UPC                    | 814964 338594  |

