

Pro-Ject Pre Box SE

Pre-amplifier with remote control



Good sound from sound technology

- Metal case shields the electronics from vibrational and electromagnetic interference
- Optimal channel separation through dual-mono circuitry
- Special low-noise ICs used
- Gold plated RCA connection sockets
- Outboard power supply included

Features

- Remote controllable
- Small size allows easy placement
- Display dimmable
- Four line level inputs
- Record- and subwoofer output
- Remote power switching for connected units via on/off switch (Trigger)

Technical specifications

Frequency response:	20Hz - 20kHz ($\pm 0,2$ dB)
Noise floor:	-94dB (A weighted)
THD:	0,005%
Gain:	12dB
Pre out:	1 pair RCA/Phono sockets
Output voltage typically:	1V at 1kHz
Record and subwoofer out:	RCA/Phono sockets
Line-level inputs:	4 pairs RCA/Phono sockets
Input impedance:	100kohms
Trigger:	12V DC switching voltage
Trigger output:	2-pole 2,5mm \varnothing co-axial jack
Outboard power supply:	16V/1.000mA AC, suitable for your country's mains supply
Power consumption:	16V/200mA AC
Replacement battery remote control:	1 x CR 2032 / 3V
Dimensions (W x H x D):	103 x 72 x 150mm
Weight:	1.200g without power supply

The manufacturer reserves the right to alter the technical specifications without notice.



Available in silver or black finish