Stereo Box DS

Stereo integrated amplifier

- Dual mono design
- 2 power modules for each channel
- 2 ohms drive capability
- 4 stereo line inputs (RCA)
- Digital input: USB
- Big elegant control display
- Familiar sound with Stereo Box S with higher power output
- Metal case shields the electronics from vibrational and electromagnetic interference
- Faceplate silver or black

Technical data

Power output	2x 40W / 60W at 8 / 4 ohms 2 ohms drive capability
Signal-to-noise ratio	> -90dB (IEC -A)
Channel separation	> 40dB at 20kHz
Frequency response	10Hz - 50kHz (+0dB, -3)
THD	0,1% / 35W
Gain	26dB
Digital input	USB 1.1 (Mini USB B)
DA converter	PCM 2706
Stereo line inputs	4 pair RCA/Cinch sockets
Input impedance	100 kohms
Speaker connectors	4mm Ø banana plugs, spades connectors or naked wire
Power supply	24V/5A DC; 120 - 240V, 50/60Hz
Standby Power consumption	<1 Watt
Dimensions W x H x D	103 x 72 x 144 (163) mm (D with sockets)
Weight	1180g without power supply

Stereo Box DS integrated amplifier

Audiophile-grade integrated amplifier with dual mono construction uses only best quality PWM amplifier modules. Sound quality is similar to Stereo Box S, but usage of 2 modules per channel brings enough power, even for demanding speakers. Additionally Stereo Box DS is 2 ohm capable.
4 stereo line level inputs (RCA) and 1 digital USB input offer a lot of connection options. The big, elegant & easy to read-out control display combined with control buttons on front or IR remote makes usage a piece of cake. The massive metal casing protects against interference.
Stereo Box DS is available in silver or black and comes with dedicated IR remote.

< Black version

Back view >

- ◊ Digital Input (USB)
- ◊ RCA Stereo
- ◊ speaker outputs
- ◊ Power

PRO-JECT AUDIO SYSTEMS
a division of AUDIO TUNING GmbH
1050 Wien, Margaretenstraße 98,