

Pro-Ject RPM 10

Manual turntable with
10" tonearm and
base Ground it deluxe



Turntable

- Chassis and particle filled base Ground it piano-lacquered dark grey
- A quiet running AC motor with a two-step acryl pulley drives the platter's outside edge via a belt.
- The medium density fibre plinth stands on three height-adjustable Sorbotane®-damped aluminium cones. Particle filled plinth guarantees constant damping. A supplied spirit level allows easy adjustment.
- The motor is mounted in a separate metal housing to eliminate vibration transmission.
- The resonance-optimised platter is a sandwich construction utilising an acrylic platter weighing 5,4Kg and a brass record puck.
- The magnet supported, inverted bearing uses a stainless-steel axle carrying a ceramic ball on which the ceramic bearing plate runs.
- Central metal block optimises centre of gravity and damps main bearing.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

Tonearm Pro-Ject 10cc

- The headshell and armtube are fashioned from a single piece of carbon-fibre.
- Conical armtube avoids standing wave reflections.
- Inverted tonearm bearing comprises four hardened stainless tips in ABEC7 spec ballraces.
- Rings provide very solid arm bearing housings. The outside ring is open to avoid resonances.
- Design of counterweight effectively counteracts unwanted resonances.
- The counterweight supplied is suitable for cartridges weighing between 6 - 9g. Alternative counterweights for cartridges weighing between 7 - 11g and 10 - 15g are available as an accessory part.
- Counterweight shaft lowered to record level reduces cantilever forces and dynamic wow when playing warped records.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- The straight armtube with an effective length of 10" reduces toe-in error.
- Silicone-damped armlift can be adjusted to suit working height of the arm.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions turntable, W x H x D: Including motor unit 210 x 480 x 330mm.

Dimensions base Ground it, W x H x D: 65 x 500 x 400mm including spikes. H without spikes 45mm.

Dust cover Cover it optional, W x H x D: 525 x 290 x 425mm.

The manufacturer reserves the right to alter the technical specifications without notice.